Serial No. 10/709,675 Filed: May 21, 2004 Page 2 of 28 Examiner: Nicole R. Blan Group Art Unit: 1792

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

- (Canceled)
- (Currently Amended) The household clothes washer according to claim 30, wherein a predetermined range of motion defines the an operational condition of the boot.
- 3. (Currently Amended) The household clothes washer according to claim 2, wherein the boot is in the non-isolating condition when the a magnitude of the forces acting on the washer as the basket rotates about a horizontal axis is such that the top of the cabinet moves through an arc no greater than 2 inches.
- (Previously Presented) The household clothes washer according to claim
 wherein first physical shape is a natural state and the second physical shape is a collapsed state.
- (Currently Amended) The household clothes washer according to claim 4, wherein the boot-comprises a-snubber is spaced above the floor when the boot is in the natural state and compressed against the floor when the boot is in the collapsed state.
 - (Canceled)
- (Currently Amended) The household clothes washer according to claim 630, wherein the sole comprises a snubber recess that opens onto the bottom surface, with the snubber extending into the recess.

 Serial No. 10/709,675
 Examiner: Nicole R. Blan

 Filed: May 21, 2004
 Group Art Unit: 1792

 Page 3 of 28
 Page 3 of 28

 (Original) The household clothes washer according to claim 7, and further comprising a stiffener in the sole.

- (Original) The household clothes washer according to claim 8, wherein
 the stiffener circumscribes the snubber recess.
- 10. (Original) The household clothes washer according to claim 9, wherein the upper terminates in a resilient shoulder defining a mouth for the foot recess, with the mouth having a portion smaller than the foot such that when the foot passes through the mouth, the resilient shoulder is initially deflected and when the foot is received in the recess, the resilient shoulder overlies a portion of the foot to aid in mounting the boot to the foot.
- (Currently Amended) The household clothes washer according to claim
 and further comprising a retaining element for retaining the foot beneath the shoulder.
- (Original) The household clothes washer according to claim 11, wherein the retaining element is a split element substantially circumscribing the mouth.
- 13. (Original) The household clothes washer according to claim 12, and further comprising a bearing plate positioned within the foot recess and supporting the foot relative to the boot when the foot is received within the foot recess.
 - (Canceled)
 - 15. (Canceled)
- (Currently Amended) The household clothes washer according to claim 4530, and further comprising a stiffener in the sole.
- (Currently Amended) The household clothes washer according to claim 4530, and further comprising a retaining element for helping to retain the foot in the upper.

 Serial No. 10/709,675
 Examiner: Nicole R. Blan

 Filed: May 21, 2004
 Group Art Unit: 1792

 Page 4 of 28
 Page 4 of 28

18. (Currently Amended) The household clothes washer according to claim +530, and further comprising a bearing plate positioned within the foot recess and supporting the foot relative to the boot when the foot is received within the foot recess.

- (Previously Presented) The household clothes washer according to claim
 wherein the boot is made from a resilient material.
- (Original) The household clothes washer according to claim 19, wherein the basket rotates about a horizontal axis.

21. (Canceled)

- 22. (Previously Presented) The household appliance according to claim 31, wherein the boot comprises a sole with a bottom surface for contacting the floor, and an upper extending from the sole and defining a foot recess in which the foot is received to mount the boot to the foot.
- 23. (Previously Presented) The household appliance according to claim 22, wherein the boot comprises a snubber extending from the sole and spaced above the floor when the boot is in the isolating condition and compressed against the floor when the boot is in the non-isolating condition.
- (Original) The household appliance according to claim 22, and further comprising a stiffener in the sole.
- 25. (Original) The household appliance according to claim 22, and further comprising a retaining element for retaining the foot in the upper.
- (Original) The household appliance according to claim 25, wherein the retaining element is a split element substantially circumscribing the upper.

 Serial No. 10/709,675
 Examiner: Nicole R. Blan

 Filed: May 21, 2004
 Group Art Unit: 1792

Page 5 of 28

27. (Original) The household appliance according to claim 22, and further comprising a bearing plate positioned within the foot recess and supporting the foot relative to the boot when the foot is received within the foot recess.

- 28. (Original) The household appliance according to claim 22, wherein a predetermined range of motion defines the operational condition of the boot.
- 29. (Original) The household appliance according to claim 28, wherein the boot is in the non-isolating condition when the magnitude of the forces acting on the washer as the basket rotates about a horizontal axis is such that the top of the cabinet moves through an arc no greater than 2 inches.
- (Currently Amended) A household clothes washer for use in a home environment having a floor for supporting the household clothes washer, comprising:
 - a wash basket mounted within the cabinet for rotational motion:
 - a foot extending from the cabinet for supporting the cabinet on the floor;

and

a solid-body elastomeric boot comprising:

a cabinet:

-an upper defining a foot recess in which the foot is removably received to couple the boot to the foot,

a sole configured to be in contact with the floor when the boot is in an isolating and non-isolating condition,

a snubber configured to be in contact with the floor when the boot is in a non-isolating condition and out of contact with the floor when the boot is in an isolating condition, and

the boot is deformable such that the snubber moves relative to the foot as the boot is deformed between a first physical shape corresponding Serial No. 10/709,675 Filed: May 21, 2004 Page 6 of 28 Examiner: Nicole R. Blan Group Art Unit: 1792

to thean isolating condition, where the <u>snubber is out of contact with the floor and the</u> boot substantially isolates the floor from forces generated by the rotation of the basket and acting through the foot, and a second physical shape corresponding to the non-isolating condition, where the <u>snubber is in contact with the floor and the</u> boot substantially passes the forces through the foot and into the floor.

- (Currently Amended) A household appliance for use in a home environment having a floor for supporting the household appliance, comprising:
 - a cabinet:
 - a vibration generator located within the cabinet;
 - a foot extending from the cabinet for supporting the cabinet on the floor;

and

a solid-body elastomeric boot comprising:

an upper defining a foot recess in which the foot is removably received to couple the boot to the foot,

a sole configured to be in contact with the floor when the boot is in an isolating and non-isolating condition,

a snubber configured to be in contact with the floor when the boot is in a non-isolating condition and out of contact with the floor when the boot is in an isolating condition, and

the boot is deformable such that the snubber moves relative to the foot as the boot is deformed between a first physical shape corresponding to an-the isolating condition, where the snubber is out of contact with the floor and the boot substantially isolates the floor from forces generated by the rotation of the basketyibration generator and acting through the foot, and a second physical shape corresponding to a-the non-isolating

Serial No. 10/709,675 Filed: May 21, 2004 Page 7 of 28

condition, where the <u>snubber is in contact with the floor and the</u> boot substantially passes the forces through the foot and into the floor.

Examiner: Nicole R. Blan Group Art Unit: 1792